

# ALT S223 Filler (RS233 Mortar Component-B)



## Product Data Sheet

### Description

**ALT S223 Filler** is a proprietary high performance blended filler component.

### Product Use

**ALT S223 Filler** powder is mixed with ALT R210 Resin to create ALT RS233 Mortar, a trowel-able mortar used in approved ALT deck coating, surfacing and waterproofing systems.

### Color

ALT S223 Filler is supplied in a grey/beige base.

### Packaging

ALT S223 Filler is supplied in 23-kg bags.

### Coverage Rate, Mixing & Catalyzing

See ALT RS233 Mortar product data sheet for recommendations regarding specific applications, coverage rates, mixing and catalyzing. Yields will vary depending upon system selected and the smoothness and absorbency of substrate.

### Storage

Always store in cool and dry location. Do not store in direct sunlight or in temperatures below 32°F(0°C) or above 77°F(25°C). Approximate shelf life is 6-months when left sealed, unmixed and with proper storage.

### Application Conditions

This product is recommended for use at substrate and ambient temperatures between 37°F (3°C) and 95°F (35°C).

### Tool Cleaning

When work is interrupted or completed, tools must be thoroughly cleaned with ALT Activator before the resin hardens.

### Safety Recommendations

Refer to product Safety Data Sheet (SDS) prior to use or handling.

### Disposal

Product may be swept up and discarded. When combined with ALT R210 Resin, catalyzed and cured ALT RS233 resin-mortar may be disposed of in standard landfills. Uncured resin-mortar is considered a hazardous material and must be handled as such, in accordance with local, state and federal regulations.

### Ordering Information

**ALT S223 Filler**  
#118-000U                      23.0 kg bag

### Remarks/Comments

The information provided regarding application of ALT Global products is based on extensive development work, as well as many years of experience, and is given to the best of our knowledge. However, due to the diverse conditions encountered in building construction, it is necessary for the contractor to test the product for its suitability in any given case. We reserve the right to make alterations in keeping with technical developments or improvements.

### DISCLAIMER

NO WARRANTY, EXPRESS OR IMPLIED, IS MADE IN THIS DOCUMENT. THE PRODUCT IS NOT CLAIMED TO BE MERCHANTABLE OR FIT FOR ANY PARTICULAR PURPOSE. User and certified ALT Global system applicators determine suitability only. See individual ALT Global System product data sheets, SDS sheets, guide specifications and details for complete information regarding the suitability, application and handling of ALT Global System products.