



ALT R230 THIXO MEMBRANE WALL FLASHING (TYP.)

ALT R230 THIXO MEMBRANE COLLAR CUT TO FIT DIAMETER OF PIPE RAILING.

ALT R230 THIXO MEMBRANE FINGER FLASHING WRAPPED AROUND PIPE W/ 1" MINIMUM OVERLAP.

ALUMINUM OR STEEL PIPE RAILING SYSTEM W/ WATERTIGHT CONNECTIONS & INTEGRAL MOUNTING PLATE ANCHORED TO STRUCTURE AS REQUIRED (BY OTHERS)

EXTEND SURFACE PREP MAX. 1/8" BEYOND LINE OF ALT FLASHING & COVER W/PAINT AS REQ'D.

POWER TOOL CLEAN RAILING POST & MOUNTING PLATE PER SSPC-SP3.

PREPARE, LEVEL & PATCH SUBSTRATE W/ALT R290 PASTE OR RS242 MORTAR AFTER PRIMING & PRIOR TO APPLICATION OF ALT R230 THIXO MEMBRANE (TYP.)

1" (MIN.)

4" (10cm) (MIN.)

DRAWING NO.:

M-2H

AM_02H

FLASHING @ WALL MOUNTED RAILING

REVISION	0	ISSUE DATE	10-15-2014	SCALE	N.T.S.	DRAWN BY	ALT Global
----------	---	------------	------------	-------	--------	----------	------------



ALT