



ALT R230 THIXO MEMBRANE EXTENDED OVER INTERIOR FACE OF BACK ANGLE.

WINDOW, SILL, FRAME, RECEIVER & BACK-STOP BY OTHERS (TYP.)

SHIM SET-IN ACCEPTABLE SEALANT (BY OTHERS)

TRIM FLASHING & SEALANT AS REQUIRED (BY OTHERS)

ALT R230 THIXO FLASHING APPLIED OVER SUBSTRATE PROPERLY PREPARED & PRIMED W/APPROPRIATE ALT PRIMER.

NOTE: FASTENERS SHOULD NOT PENETRATE ALT R230 THIXO MEMBRANE FLASHING. ANY PENETRATIONS MADE THRU MEMBRANE ARE EXCLUDED FROM WARRANTY COVERAGE.

PREPARE, LEVEL & PATCH SUBSTRATE W/ALT R290 PASTE OR RS242 MORTAR AFTER PRIMING & PRIOR TO APPLICATION OF ALT R230 THIXO MEMBRANE (TYP.)

(1) PLY ALT R230 THIXO MEMBRANE FLASHING EXTEND 4" MIN. HORIZONTALLY ONTO PREPARED & PRIMED SUBSTRATE.

ASSURE FULL RESIN SATURATION OF FLEECE & CONTACT W/SUBSTRATE.

ALT R230 FIELD MEMBRANE

8" (20 cm) MIN. RECOMMENDED

4" (10 cm)  
(MIN.)

DRAWING NO.:

**M-2B**

AM\_02B

**NEW WINDOW SILL FLASHING**

REVISION	0	ISSUE DATE	10-15-2014	SCALE	N.T.S.	DRAWN BY	ALT Global
----------	---	------------	------------	-------	--------	----------	------------



**ALT**