



POLYURETHANE CAULKING
(BY OTHERS)

COUNTERFLASHING AS REQUIRED
(BY OTHERS)

ALT R230 THIXO MEMBRANE TARGET PATCH
APPLIED OVER SCUPPER OPENING

PREPARE, LEVEL & PATCH SUBSTRATE
W/ALT R290 PASTE OR RS242 MORTAR
AFTER PRIMING & PRIOR TO APPLICATION
OF ALT R230 MEMBRANE (TYP.)

ALT R230 RESIN BEAD TYPICAL @ ALL
MEMBRANE TERMINATION POINTS

ALT R230 THIXO MEMBRANE 2" MINIMUM OVERLAP
TO PROVIDE CONTINUOUS FLASHING

(1) PLY ALT R230 THIXO MEMBRANE FLASHING
EXTEND INTO PREPARED & PRIMED TUBE W/
OVERLAP 2" TO FORM SCUPPER FLASHING

ASSURE FULL RESIN SATURATION OF
FLEECE & CONTACT W/SUBSTRATE.

ALT R230 MEMBRANE FIELD

NOTE:
METAL OR PVC SCUPPER SLEEVE THRU
WALL BY OTHERS. FOR SCUPPERS CAST IN
CONCRETE TO BE LINED W/ALT MEMBRANE
PROVIDE 4" X 4" MINIMUM OPENING (TYP.)

DRAWING NO.:

D-1D

AD_01D

**PREFABRICATED TUBE THRU-WALL
OVERFLOW SCUPPER FLASHING**

REVISION	0	ISSUE DATE	10-15-2014	SCALE	N.T.S.	DRAWN BY	ALT Global
----------	---	------------	------------	-------	--------	----------	------------



ALT