

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

* 1 Identification

- **Product identifier**
- **Trade name:** ALT WeTraffic 491
- **Article number:** 329-xxx-yyyU
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

ALT Global, LLC
12 Dwight Place
Fairfield, NJ 07004
USA
Tel.: +1 973-287-6158
Fax: +1 973-287-6168
Internet: www.altglobal.com

- **Information department:**

Division product safety
Mr. Bonyadlou
Tel.: +1 973-287-6158
E-Mail: mbonyadlou@altglobal.com

- **Emergency telephone number:**

For Chemical Emergency
Spill Leak Fire Exposure or Accident
Call CHEMTREC Day or Night

DOMESTIC NORTH AMERICA 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 1)

· **Hazard-determining components of labeling:**

2-ethylhexyl acrylate
 titanium dioxide
 methyl methacrylate
 n-butyl acrylate

· **Hazard statements**

H225 Highly flammable liquid and vapor.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P261 Avoid breathing vapours.
 P280 Wear protective clothing/ eye protection.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P403+P235 Store in a well-ventilated place. Keep cool.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
 Fire = 3
 Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1
 Fire = 3
 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|---|-----------------------|------------|
| CAS: 103-11-7 Index number: 607-107-00-7 | 2-ethylhexyl acrylate | 10-25% |
| CAS: 80-62-6 Index number: 607-035-00-6 | methyl methacrylate | ≥2.5-<10% |
| CAS: 141-32-2 Index number: 607-062-00-3 | n-butyl acrylate | ≥2.5-<10% |
| CAS: 13463-67-7 | titanium dioxide | ≥0.1-≤2.5% |

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: **ALT WeTraffic 491**

(Contd. of page 2)

Take affected persons out of danger area and lay down.

Involve doctor immediately.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

Seek medical treatment.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Skin sensitization.

Irritant to skin, eyes and respiratory system.

· **Indication of any immediate medical attention and special treatment needed**

After inhalation, even in the absence of signs of disease, inhaled corticosteroid (eg Ventolair) give.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder, foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

Vapours are heavier than air.

Crawling vapors can result in greater distance from the ignition!

· **Advice for firefighters**

· **Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation



Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 3)

· **Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|-------------|---------------------------------|-------------------------|
| 21645-51-2 | aluminium hydroxide | 8.7 mg/m ³ |
| 103-11-7 | 2-ethylhexyl acrylate | 15 ppm |
| 80-62-6 | methyl methacrylate | 17 ppm |
| 1309-37-1 | diiron trioxide | 15 mg/m ³ |
| 141-32-2 | n-butyl acrylate | 8.3 ppm |
| 13463-67-7 | titanium dioxide | 30 mg/m ³ |
| | PEG 200 DMA | 30 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 0.075 mg/m ³ |
| 112945-52-5 | SYNTHETIC AMORPHOUS SILICA | 18 mg/m ³ |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 50 ppm |
| 107-98-2 | 1-methoxy-2-propanol | 100 ppm |
| 123-86-4 | n-butyl acetate | 5 ppm |
| 97-88-1 | n-butyl methacrylate | 19 mg/m ³ |

· **PAC-2:**

| | | |
|-------------|---------------------------------|-----------------------|
| 21645-51-2 | aluminium hydroxide | 73 mg/m ³ |
| 103-11-7 | 2-ethylhexyl acrylate | 120 ppm |
| 80-62-6 | methyl methacrylate | 120 ppm |
| 1309-37-1 | diiron trioxide | 360 mg/m ³ |
| 141-32-2 | n-butyl acrylate | 130 ppm |
| 13463-67-7 | titanium dioxide | 330 mg/m ³ |
| | PEG 200 DMA | 330 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 33 mg/m ³ |
| 112945-52-5 | SYNTHETIC AMORPHOUS SILICA | 100 mg/m ³ |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1,000 ppm |
| 107-98-2 | 1-methoxy-2-propanol | 160 ppm |
| 123-86-4 | n-butyl acetate | 200 ppm |
| 97-88-1 | n-butyl methacrylate | 210 mg/m ³ |

· **PAC-3:**

| | | |
|-------------|----------------------------|-------------------------|
| 21645-51-2 | aluminium hydroxide | 440 mg/m ³ |
| 103-11-7 | 2-ethylhexyl acrylate | 150 ppm |
| 80-62-6 | methyl methacrylate | 570 ppm |
| 1309-37-1 | diiron trioxide | 2,200 mg/m ³ |
| 141-32-2 | n-butyl acrylate | 480 ppm |
| 13463-67-7 | titanium dioxide | 2,000 mg/m ³ |
| | PEG 200 DMA | 2,000 mg/m ³ |
| 14808-60-7 | Quartz (SiO ₂) | 200 mg/m ³ |
| 112945-52-5 | SYNTHETIC AMORPHOUS SILICA | 630 mg/m ³ |

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

| | | |
|----------|---------------------------------|-------------------------|
| | | (Contd. of page 4) |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm |
| 107-98-2 | 1-methoxy-2-propanol | 660 ppm |
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 97-88-1 | n-butyl methacrylate | 1,300 mg/m ³ |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.
 Do not refill residue into storage receptacles.
 Ensure good ventilation/exhaustion at the workplace.
 at least 7-fold air changes per hour
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Highly volatile, flammable constituents are released during processing.
 Keep ignition sources away - Do not smoke.
 Fumes can combine with air to form an explosive mixture.
 Only explosion-proof equipment.
 Protect against electrostatic charges.
 Protect from heat.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Store only in the original receptacle.
 Store in a cool location.
- **Information about storage in one common storage facility:**
 Store away from oxidizing agents.
 Store away from foodstuffs.
- **Further information about storage conditions:**
 Store in cool, dry conditions in well sealed receptacles.
 Storage in a collecting room is required.
 Store under lock and key and with access restricted to technical experts or their assistants only.
 max. Storage temperature 30 ° C
 Keep receptacle tightly sealed.
 Protect from heat and direct sunlight.
- **Specific end use(s)** Building coating or sealing.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

| | |
|---|--|
| 80-62-6 methyl methacrylate (≥2.5-<10%) | |
| PEL | Long-term value: 410 mg/m ³ , 100 ppm |

(Contd. on page 6)
US

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 5)

| | |
|---|--|
| REL | Long-term value: 410 mg/m ³ , 100 ppm |
| TLV | Short-term value: 410 mg/m ³ , 100 ppm Long-term value: 205 mg/m ³ , 50 ppm DSEN |
| 141-32-2 n-butyl acrylate (≥2.5-<10%) | |
| REL | Long-term value: 55 mg/m ³ , 10 ppm |
| TLV | Long-term value: 11 mg/m ³ , 2 ppm DSEN |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Avoid contact with the eyes and skin.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Keep away from foodstuffs, beverages and feed.

· **Breathing equipment:**

- Ensure good ventilation.
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Check protective gloves prior to each use for their proper condition.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

· **Material of gloves**



Butyl rubber gloves - butyl e.g. KCL BUTOJET
 Recommended thickness of the material: ≥ 0.7 mm
 Breakthrough time: ≥ 480 min

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Butyl rubber, BR

· **For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR

· **Not suitable are gloves made of the following materials:** Leather gloves

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 6)

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Color: Different according to coloring

· **Odor:** after MMA

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Undetermined.

· **Flash point:** 18 °C (64.4 °F) (DIN EN ISO 3679:2015-06)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 252 °C (485.6 °F) (2-EHA)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
 Not determined.

· **Explosion limits:**

Lower: 0.9 Vol % (2-EHA)
 Not determined.

Upper: 6.4 Vol % (2-EHA)
 Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 1.74 g/cm³ (14.52 lbs/gal) (EN ISO 2811-1)

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** log Pow: 4,29 (2-EHA); (25 °C, OECD 107)
 log Pow: 1,38 (MMA)
 log Kow 2,38 (25 °C) (BA)

· **Viscosity:**

Dynamic at 20 °C (68 °F): 3,000 mPas (EN ISO 2555)

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 7)

| | |
|----------------------------|--|
| · Solvent content: | |
| Organic solvents: | 0.1 % |
| Water: | 5.0 % |
| VOC content: | 2.64 % |
| | 50.3 g/l / 0.42 lb/gal |
| · Solids content: | |
| | 79.8 % |
| · Other information | |
| | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** see Section 10.2
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Exothermic reaction.
Reacts with peroxides and other radical forming substances.
A hazardous polymerization may occur after the exhaustion of the inhibitor.
- **Conditions to avoid** Avoid heat. Avoid direct sunlight.
- **Incompatible materials:** Heftige Reaktionen mit Peroxiden und anderen Reduktionsmittel
- **Hazardous decomposition products:**
No dangerous decomposition products used according to specifications.
- **Additional information:**
Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

11 Toxicological information

- **Information on toxicological effects** There were no toxicological findings to the mixture.
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

| | | |
|------------|---------|-----------------------|
| Oral | LD50 | >11,935 mg/kg (rat) |
| Dermal | LD50 | 79,514 mg/kg (rabbit) |
| Inhalative | LC50/4h | >149 mg/l (rat) |

21645-51-2 aluminium hydroxide

| | | |
|------------|-------|-----------------------------|
| Oral | LD50 | >2,000 mg/kg (rat) |
| | NOAEL | 30 mg/kg (rat) chronisch |
| Inhalative | LC50 | 7.6 mg/l (rat) |
| | NOAEC | 70 mg/m ³ (rat) |

103-11-7 2-ethylhexyl acrylate

| | | |
|--------|------|-------------------------------|
| Oral | LD50 | 4,435 mg/kg (rat) (BASF-Test) |
| Dermal | LC50 | 7,520 mg/kg (hare) |

80-62-6 methyl methacrylate

| | | |
|------|-------|---|
| Oral | LD50 | >5,000 mg/kg (rat) (OECD 401) |
| | NOAEL | 2,000 ppm (rat) drinking water, 6-2000 ppm Findings: No toxic effects |

(Contd. on page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 8)

| | | |
|------------------------------------|---------|---|
| Dermal | LC50 | >5,000 mg/kg (rabbit) |
| Inhalative | NOAEL | 25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm |
| | LC50/4h | 29.8 mg/l (rat) |
| 141-32-2 n-butyl acrylate | | |
| Oral | LD50 | 3,150 mg/kg (rat) (BASF-Test) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) (sonstiges) |
| Inhalative | LC50/4h | 10.3 mg/l (rat) (Staub) geprüft wurde der Dampf |
| 13463-67-7 titanium dioxide | | |
| Oral | LD50 | >20,000 mg/kg (rat) |
| Dermal | LC50 | >10,000 mg/kg (hare) |
| Inhalative | LC50/4h | >6.82 mg/l (rat) |

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Other information (about experimental toxicology):**

Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.

· **Subacute to chronic toxicity:** not tested

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|------------|----------------------------|----|
| 103-11-7 | 2-ethylhexyl acrylate | 3 |
| 80-62-6 | methyl methacrylate | 3 |
| 1309-37-1 | diiron trioxide | 3 |
| 141-32-2 | n-butyl acrylate | 3 |
| 13463-67-7 | titanium dioxide | 2B |
| 14808-60-7 | Quartz (SiO ₂) | 1 |
| 128-37-0 | Butylated hydroxytoluene | 3 |

· **NTP (National Toxicology Program)**

| | | |
|------------|----------------------------|---|
| 14808-60-7 | Quartz (SiO ₂) | K |
|------------|----------------------------|---|

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

80-62-6 methyl methacrylate

EC3/16h 100 mg/l (Pseudomonas putida) (Cell proliferation inhibition test, Bringmann-Kühn)

· **Aquatic toxicity:**

21645-51-2 aluminium hydroxide

EC50 >100 mg/l (daphnia magna)

(Contd. on page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 9)

| | |
|---------------------------------------|--|
| LC50 | >100 mg/l (Selenastrum capricornutum) >100 mg/l (Salmo trutta) |
| 103-11-7 2-ethylhexyl acrylate | |
| other (28d) | >1,000 mg/kg (Soil microorganisms) (OECD 217) The product has not been tested. The statement has been derived from products of a similar structure or composition. |
| EC50/48h (static) | 1.3 mg/l (daphnia magna) (OECD-Richtline 202) Part 1 |
| LC50/96h (static) | 1.81 mg/l (Rainbow trout) (OECD 203) |
| NOEC/21d | 0.19 mg/l (daphnia magna) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition. |
| EC50/72h (static) | 1.71 mg/l (scenedesmus subspicatus) (OECD 201) Die Angaben der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration. |
| 80-62-6 methyl methacrylate | |
| EC50/48h | 69 mg/l (daphnia magna) (OECD 202) |
| LC50/96h | >79 mg/l (Rainbow trout) (OECD 203) |
| ErC50/72h | >110 mg/l (Pseudokirchneriella subcapitata) (OECD 201) |
| NOEC/72h | >110 mg/l (Selenastrum capricornutum) (OECD 201) |
| EC50/72h | >110 mg/l (Selenastrum capricornutum) (OECD 201) |
| NOEC | 9.4 mg/l (Danio rerio) (OECD 210) fish early life stage test, 35 days 37 mg/l (daphnia magna) (OECD 211) 21 days |
| 141-32-2 n-butyl acrylate | |
| EC0/3d | >150 mg/l (Bel) (industriell (aerob)) |
| other (28d) | >1,000 mg/kg (BMO) (OECD 217) Das Produkt wurde nicht geprüft. die Aussage wurde von Produkte ähnlicher Struktur oder Zusammensetzung abgeleitet. Die Angabe der toxischen Wirkung bezieht sich auf die Nominalkonzentration. |
| EC50/48h | 8.2 mg/l (daphnia magna) (OECD-Richtline 202) Die Angabe der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration. |
| NOEC/21d (static) | 0.136 mg/l (daphnia magna) (OECD 211) Die Angabe der toxischen Wirkung bezieht sich auf analytisch ermittelte Konzentrationen. |
| EC50/96h (static) | 2.65 mg/l (Selenastrum capricornutum) (OECD 201) Die Angabe der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration. 2.1 mg/l (w) (OECD guideline 203, flow rate) Die Angabe der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration. |
| EC20/0,5h | >1,000 mg/l (Bel) (OECD 209) Das Produkt wurde nicht geprüft. Die Aussage wurde von Produkte ähnlicher Struktur oder Zusammensetzung abgeleitet. |

- **Persistence and degradability** Easily biodegradable
- **Other information:** The product is easily biodegradable.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** May be accumulated in organism

(Contd. on page 11)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 10)

- **Mobility in soil**
 MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. Where the substance into the environment he verleiht preferably in the compartment into which it has emerged.
 2-EHA: The product floats on water and does not dissolve. Adsorption on soil is not likely.
- **Additional ecological information:**
- **CSB-value:** 2-EHA: Theoretical oxygen demand (TOD) = 5.6 g/g
- **BSB5-value:** 0.14 g/g (MMA)
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.
- **Recommendation:**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.
 Cured product residues are not hazardous waste.

- **Uncleaned packagings:**
- **Recommendation:**
 This product (liquid) and its container must be disposed of as hazardous waste.
 Disposal must be made according to official regulations.

14 Transport information

| | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p style="margin: 0;">UN1263</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA | <p style="margin: 0;">Paint 1263 PAINT PAINT</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center; margin: 10px 0;"> </div> |
| <ul style="list-style-type: none"> · Class | <p style="margin: 0;">3 Flammable liquids</p> |

(Contd. on page 12)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 11)

| | |
|---|---|
| · Label | 3 |
| · ADR | |
|  | |
| · Class | 3 (F1) Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | - |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Remarks: | Classification according to viscosity clause [(173.120 (2) (d) and 173.121 (b) (iv)] |
| · ADR | |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml > 450 litres Packing group II |
| · Remarks: | Classification according to viscosity clause (2.2.3.1.4) |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml > 450 litres Packing group II |
| · Remarks: | Classification according to viscosity clause (2.3.2.2) |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III |

US —

(Contd. on page 13)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 12)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

80-62-6 methyl methacrylate

141-32-2 n-butyl acrylate

· **TSCA (Toxic Substances Control Act):**

| | | |
|------------|---|--------|
| 21645-51-2 | aluminium hydroxide | ACTIVE |
| 103-11-7 | 2-ethylhexyl acrylate | ACTIVE |
| 80-62-6 | methyl methacrylate | ACTIVE |
| 7732-18-5 | water, distilled, conductivity or of similar purity | ACTIVE |
| 1309-37-1 | diiron trioxide | ACTIVE |
| 141-32-2 | n-butyl acrylate | ACTIVE |
| 13463-67-7 | titanium dioxide | ACTIVE |
| | PEG 200 DMA | ACTIVE |
| 14808-60-7 | Quartz (SiO ₂) | ACTIVE |
| 8002-74-2 | Paraffin waxes and Hydrocarbon waxes | ACTIVE |
| 84170-74-1 | Neopentylglycol propoxylated diacrylate | ACTIVE |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | ACTIVE |
| 107-98-2 | 1-methoxy-2-propanol | ACTIVE |
| 128-37-0 | Butylated hydroxytoluene | ACTIVE |
| 123-86-4 | n-butyl acetate | ACTIVE |
| 3147-75-9 | 2-(2H-benzotriazol-2-yl)-4-(1,1,3,3-tetramethylbutyl)phenol | ACTIVE |
| | Silan, dichlordimethyl-, Reaktionsprodukte mit Siliciumdioxid | ACTIVE |
| 97-88-1 | n-butyl methacrylate | ACTIVE |

· **Hazardous Air Pollutants**

80-62-6 methyl methacrylate

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

80-62-6 methyl methacrylate E, NL

· **TLV (Threshold Limit Value established by ACGIH)**

80-62-6 methyl methacrylate A4

(Contd. on page 14)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 13)

| | | |
|---|----------------------------|----|
| 1309-37-1 | diiron trioxide | A4 |
| 141-32-2 | n-butyl acrylate | A4 |
| 13463-67-7 | titanium dioxide | A4 |
| 14808-60-7 | Quartz (SiO ₂) | A2 |
| 128-37-0 | Butylated hydroxytoluene | A4 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | | |
| 13463-67-7 | titanium dioxide | |
| 14808-60-7 | Quartz (SiO ₂) | |

· National regulations:

· Information about limitation of use:

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* 16 Other information

These figures relate to the product as delivered.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Training hints

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555). Instruction must take place before the start of employment and at least annually thereafter.

· Date of preparation / last revision 08/18/2020 / -

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 15)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/18/2020

Reviewed on 08/18/2020

Trade name: ALT WeTraffic 491

(Contd. of page 14)

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **Sources**

www.gestis.de
www.echa.eu
logkow.cisti.nrc.ca

· * **Data compared to the previous version altered.**

US —