

ALT Thixo Liquid Additive



Product Data Sheet

Description

ALT Thixo Liquid is a thixotropic additive for ALT PMMA based resins as recommended.

Applications

ALT Thixo Liquid is mixed with ALT PMMA resins as required for application on slopes greater than 1-1/2:12 or ALT R230 Resin when used for flashings applications.

Color

ALT Thixo Liquid is supplied as an amber liquid. When mixed with recommended ALT resins, the additive becomes fully blended and takes on the color of the base resin.

Packaging

ALT Thixo Liquid is supplied in 1-kg bottles.

Mixing Ratio

ALT Thixo Liquid is added to recommended ALT resins by weight as follows:

Product/Resin	Thixo Addition (Max.)
ALT Finish 288, 220 Clear	1%
ALT R230, ALT RS233	2%
ALT RS291, ALT R268	1%
ALT R354, ALT R359	2%

Coverage Rate

Refer to "ALT" resin product data sheet for coverage rate and recommendations for specific applications. Yields will vary depending upon system selected and the smoothness and absorbency of substrate.

Storage

Always store in cool and dry location. Do not store in direct sunlight or in temperatures below 32°F (0°C) or above 77°F (25°C). Approximate shelf life is 6-months when left sealed, unmixed and with proper storage.

Application Conditions

Refer to the "ALT" resin product data sheet for coverage rate and recommendations for specific applications.

Mixing

Thoroughly mix the entire drum of resin for 2-3 minutes before each use, and prior to pouring off resin into a second container if batch mixing. Add ALT Thixo Liquid to the resin component, stir for 2-minutes using a slow-speed mechanical agitator. Allow resin to stand approximately 20-minutes with thixo agent before use. Refer to specific "ALT" resin product data sheet for recommendations regarding catalyzing and application of resin.

Working Times

Storage and working times are not affected by addition of this additive. Refer to the "ALT" resin product data sheet for specific working times.

Safety Recommendations

Refer to product Safety Data Sheet (SDS) prior to use or handling.

Disposal

When mixed with resin, catalyzed and cured resin may be disposed of in standard landfills. ALT Thixo Liquid is considered a hazardous material and must be handled as such, in accordance with local, state and federal regulations.

Ordering Information

ALT Thixo Liquid

#133-000-120U

1-kg bottle

DISCLAIMER

NO WARRANTY, EXPRESS OR IMPLIED, IS MADE IN THIS DOCUMENT. THE PRODUCT IS NOT CLAIMED TO BE MERCHANTABLE OR FIT FOR ANY PARTICULAR PURPOSE. User and certified ALT Global system applicators determine suitability only. See individual ALT Global System product data sheets, SDS sheets, guide specifications and details for complete information regarding the suitability, application and handling of ALT Global System products.