

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

* 1 Identification

- **Product identifier**
- **Trade name: ALT Metal Primer**
- **Article number:** 117-790-110U
- **Application of the substance / the mixture** Priming
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

ALT Global, LLC
12 Dwight Place
Fairfield, NJ 07004
USA
Tel.: +1 973-287-6158
Fax: +1 973-287-6168
Internet: www.altglobal.com

- **Information department:**

Division product safety
Mr. Bonyadlou
Tel.: +1 973-287-6158
E-Mail: mbonyadlou@altglobal.com

- **Emergency telephone number:**

For Chemical Emergency
Spill Leak Fire Exposure or Accident
Call CHEMTREC Day or Night

DOMESTIC NORTH AMERICA 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

2-methoxy-1-methylethyl acetate
ethyl acetate

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: **ALT Metal Primer**

(Contd. of page 1)

· **Hazard statements**

- H225 Highly flammable liquid and vapor.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

· **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P280 Wear protective gloves/ eye protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P312 Call a poison center/doctor if you feel unwell.
- P403+P235 Store in a well-ventilated place. Keep cool.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 108-65-6 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate	10-25%
CAS: 141-78-6 Index number: 607-022-00-5	ethyl acetate	10-25%
CAS: 13463-67-7	titanium dioxide	2.5-10%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

- Immediately remove any clothing soiled by the product.
- Take affected persons out of danger area and lay down.
- Involve doctor immediately.

· **After inhalation:**

- In case of unconsciousness place patient stably in side position for transportation.
- Take affected persons into fresh air and keep quiet.
- Seek medical treatment.

· **After skin contact:**

- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: ALT Metal Primer

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
 Headache
 Dizziness
 Skin sensitization.
 Irritant to skin, eyes and respiratory system.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder, foam.
- **Special hazards arising from the substance or mixture**
 Can form explosive gas-air mixtures.
 Formation of toxic gases is possible during heating or in case of fire.
 In case of fire, the following can be released:
 Carbon monoxide (CO)
 Nitrogen oxides (NO_x)
- **Advice for firefighters**
- **Protective equipment:**
 Wear fully protective suit.
 Wear self-contained respiratory protective device.
- **Additional information**
 Cool endangered receptacles with water spray.
 Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Ensure adequate ventilation



Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.
 Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**
 Do not allow to enter sewers/ surface or ground water.
 Inform respective authorities in case of seepage into water course or sewage system.
 Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
 Do not flush with water or aqueous cleansing agents
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
141-78-6	ethyl acetate	1,200 ppm
13463-67-7	titanium dioxide	30 mg/m ³

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: ALT Metal Primer

(Contd. of page 3)

112945-52-5	SYNTHETIC AMORPHOUS SILICA	18 mg/m ³
1344-28-1	aluminium oxide	15 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
1314-23-4	zirconium oxide	14 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm

· PAC-2:

108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
141-78-6	ethyl acetate	1,700 ppm
13463-67-7	titanium dioxide	330 mg/m ³
112945-52-5	SYNTHETIC AMORPHOUS SILICA	100 mg/m ³
1344-28-1	aluminium oxide	170 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
1314-23-4	zirconium oxide	110 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppm

· PAC-3:

108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
141-78-6	ethyl acetate	10000** ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
112945-52-5	SYNTHETIC AMORPHOUS SILICA	630 mg/m ³
1344-28-1	aluminium oxide	990 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
1314-23-4	zirconium oxide	680 mg/m ³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.

Do not refill residue into storage receptacles.

Ensure good ventilation/exhaustion at the workplace.

at least 7-fold air changes per hour

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Only explosion-proof equipment.

Protect against electrostatic charges.

Protect from heat.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

· Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from foodstuffs.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: ALT Metal Primer

(Contd. of page 4)

- **Further information about storage conditions:**
 Store in cool, dry conditions in well sealed receptacles.
 Storage in a collecting room is required.
 Store under lock and key and with access restricted to technical experts or their assistants only.
 max. Storage temperature 30 ° C
 Keep receptacle tightly sealed.
 Protect from heat and direct sunlight.
- **Specific end use(s)** Building coating or sealing.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate (10-25%)

WEEL	Long-term value: 50 ppm
------	-------------------------

141-78-6 ethyl acetate (10-25%)

PEL	Long-term value: 1400 mg/m ³ , 400 ppm
-----	---

REL	Long-term value: 1400 mg/m ³ , 400 ppm
-----	---

TLV	Long-term value: 1440 mg/m ³ , 400 ppm
-----	---

112945-52-5 SYNTHETIC AMORPHOUS SILICA (≤2.5%)

OSHA PEL	Short-term value: 15 mg/m ³ Long-term value: 5 mg/m ³
----------	--

TLV-TWA	Short-term value: 10 mg/m ³ Long-term value: 3 mg/m ³ ACGIH
---------	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Avoid contact with the eyes and skin.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes.
- **Breathing equipment:**
 Ensure good ventilation.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
 Preventive skin protection by use of skin-protecting agents is recommended.
 After use of gloves apply skin-cleaning agents and skin cosmetics.
 Check protective gloves prior to each use for their proper condition.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: **ALT Metal Primer**

(Contd. of page 5)

- **Penetration time of glove material**
 Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**
 Butyl rubber, BR
- **For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR
- **Not suitable are gloves made of the following materials:** Leather gloves
- **Eye protection:**



Tightly sealed goggles

- **Body protection:**



Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Fruit-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	77 °C (170.6 °F) (Ethylacetat)
· Flash point:	5 °C (41 °F) (EN ISO 3680)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F) (1-Methoxy-2-propylacetat)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	2.1 Vol % (Ethylacetat)
Upper:	11.5 Vol % (Etylacetat)
· Vapor pressure at 20 °C (68 °F):	4.9 hPa (3.7 mm Hg) (Ethylacetat)
· Density at 20 °C (68 °F):	1.51 g/cm ³ (12.6 lbs/gal) (EN ISO 2811-1)
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: **ALT Metal Primer**

(Contd. of page 6)

· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
Dynamic at 20 °C (68 °F):	2,000 mPas (EN ISO 2555)	
· Solvent content:		
Organic solvents:	36.4 %	
VOC content:	36.39 %	
	549.4 g/l / 4.59 lb/gal	
Solids content:	64.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** see Section 10.2
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Exothermic reaction.
Reacts with peroxides and other radical forming substances.
A hazardous polymerization may occur after the exhaustion of the inhibitor.
- **Conditions to avoid** Avoid heat. Avoid direct sunlight.
- **Incompatible materials:** Heftige Reaktionen mit Peroxiden und anderen Reduktionsmittel
- **Hazardous decomposition products:**
No dangerous decomposition products used according to specifications.
- **Additional information:**
Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

11 Toxicological information

- **Information on toxicological effects** There were no toxicological findings to the mixture.
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	30,221 mg/kg (rabbit)
Dermal	LC50	>21,825 mg/kg
Inhalative	LC50/4h	>51.4 mg/l (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,500 mg/kg (rat)
Dermal	LC50	5,000 mg/kg (rat)
Inhalative	LC50/4h	35.7 mg/l (rat)
141-78-6 ethyl acetate		
Oral	LD50	4,934 mg/kg (rabbit) (OECD 401)
Dermal	LD50	>18,000 mg/kg (rabbit)
	LC50	>18,000 mg/kg (rat)
Inhalative	LC50/4h	56 mg/l (rat)

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: ALT Metal Primer

(Contd. of page 7)

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LC50	>10,000 mg/kg (hare)
Inhalative	LC50/4h	>6.82 mg/l (rat)

- **Primary irritant effect:**
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Other information (about experimental toxicology):**
Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.
- **Subacute to chronic toxicity:** not tested
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

108-65-6 2-methoxy-1-methylethyl acetate

EC50/48h	>500 mg/l (daphnia magna)
LC50/96h	100-180 mg/l (Rainbow trout)

141-78-6 ethyl acetate

EC50/24h	3,090 mg/l (daphnia magna) (DIN 38412, Part 11)
EC50/48h	164 mg/l (daphnia magna)
	3,300 mg/l (scenedesmus subspicatus)
LC50/96h	230 mg/l (fish)
	455 mg/l (pimephales promelas)
NOEC/72h	>100 mg/l (Alge (Desmodesmus subspicatus)) (OECD 201)
NOEC/21d	2.4 mg/l (daphnia magna)

- **Persistence and degradability** Easily biodegradable
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

(Contd. on page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: **ALT Metal Primer**

(Contd. of page 8)

- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.

· **Recommendation:**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.
 Cured product residues are not hazardous waste.

· **Uncleaned packagings:**

· **Recommendation:**

This material and its container must be disposed of as hazardous waste.
 Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA 	<p style="text-align: center;">UN1263</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA 	<p style="text-align: center;">Paint 1263 Paint PAINT</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="text-align: center;">  </div> <p style="text-align: center;">3 Flammable liquids 3</p>
<ul style="list-style-type: none"> · ADR, IMDG, IATA 	<div style="text-align: center;">  </div> <p style="text-align: center;">3 Flammable liquids 3</p>
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p style="text-align: center;">III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p style="text-align: center;">No</p>

(Contd. on page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: **ALT Metal Primer**

(Contd. of page 9)

<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids</p> <p style="text-align: center;">-</p> <p>F-E, S-E</p> <p style="text-align: center;">A</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Excepted quantities (EQ) · Remarks: 	<p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 1000 ml</p> <p>Classification according to viscosity clause (2.2.3.1.4)</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · Remarks: 	<p>5L</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 1000 ml</p> <p>Classification according to viscosity clause (2.3.2.3)</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1263 PAINT, 3, III</p>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1344-28-1 aluminium oxide

· **TSCA (Toxic Substances Control Act):**

108-65-6 2-methoxy-1-methylethyl acetate

141-78-6 ethyl acetate

13463-67-7 titanium dioxide

1344-28-1 aluminium oxide

7631-86-9 silicon dioxide, chemically prepared

1314-23-4 zirconium oxide

· **TSCA new (21st Century Act) (Substances not listed)**

112945-52-5 SYNTHETIC AMORPHOUS SILICA

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: ALT Metal Primer

(Contd. of page 10)

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
1344-28-1	aluminium oxide	A4
1314-23-4	zirconium oxide	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning young persons must be observed.
 Employment restrictions concerning pregnant and lactating women must be observed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* 16 Other information

These figures relate to the product as delivered.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Training hints**

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555).
 Instruction must take place before the start of employment and at least annually thereafter.

· **Date of preparation / last revision** 10/09/2018 / 32

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 12)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/09/2018

Reviewed on 09/25/2018

Trade name: ALT Metal Primer

(Contd. of page 11)

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• **Sources**

www.gestis.de
www.echa.eu
logkow.cisti.nrc.ca

• * **Data compared to the previous version altered.**

US
