

Printing date 10/09/2018 Reviewed on 11/11/2015

#### 1 Identification

· Product identifier

Trade name: <u>ALT S223 Filler</u>
 Article number: 118-000U

· Application of the substance / the mixture Filling mortar

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

ALT Global, LLC 12 Dwight Place Fairfield, NJ 07004

USA

Tel.: +1 973-287-6158 Fax: +1 973-287-6168 Internet: www.altglobal.com

Information department:

Division product safety

Mr. Bonyadlou

Tel.: +1 973-287-6158

E-Mail: mbonyadlou@altglobal.com • Emergency telephone number:

For Chemical Emergency Spill Leak Fire Exposure or Accident Call CHEMTREC Day or Night

DOMESTIC NORTH AMERICA 800-424-9300

### 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Precautionary statements
   P260 Do not breathe dust.
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

(Contd. on page 2)



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 1)

· vPvB: Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components: Void

#### 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Take affected persons out of danger area and lay down.

No special measures required.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

Seek medical treatment.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

If symptoms persist consult doctor.

Do not induce vomiting; immediately call for medical help.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Product itself does not burn fire extinguishing methods suitable to surrounding conditions.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective clothing.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

(Contd. on page 3)



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 2)

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
14808-60-7	Quartz (SiO2)	0.075 mg/m³
1344-28-1	aluminium oxide	15 mg/m <sup>3</sup>
· PAC-2:		
14808-60-7	Quartz (SiO2)	33 mg/m³
1344-28-1	aluminium oxide	170 mg/m <sup>3</sup>
· PAC-3:		
14808-60-7	Quartz (SiO2)	200 mg/m <sup>3</sup>
1344-28-1	aluminium oxide	990 mg/m³

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid release of dust into the air.

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

at least 7-fold air changes per hour

· Information about protection against explosions and fires:



Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store in dry conditions.

· Specific end use(s)

Wenn das Produkt mit anderen Stoffen gemischt wird, müssen die o.a. Sicherheitsratschläge beachtet werden, sofern die Zubereitung in einatembarer Form vorliegt.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

14808-60-7 Quartz (SiO2) (2.5-10%)

PEL Long-term value: 0.05\* mg/m³

\*resp. dust; 30mg/m3/%SiO2+2

(Contd. on page 4)



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 3)

REL Long-term value: 0.05\* mg/m<sup>3</sup>

\*respirable dust; See Pocket Guide App. A

TLV | Long-term value: 0.025\* mg/m³

\*as respirable fraction

#### 1344-28-1 aluminium oxide (≤2.5%)

PEL Long-term value: 15\*; 5\*\* mg/m³

\*Total dust; \*\* Respirable fraction

REL Long-term value: 10\* 5\*\* mg/m³

as Al\*Total dust\*\*Respirable/pyro powd./welding f.

TLV Long-term value: 1\* mg/m³ as Al; \*as respirable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Filter P2
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

Check the permeability prior to each anewed use of the glove.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Butyl rubber, BR

- · For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR
- · Not suitable are gloves made of the following materials: Leather gloves
- · Eye protection:



EN-Standard: EN 166

Body protection:



Protective work clothing



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 4)

#### 9 Physical and chemical properties

· Information on basic physical and chemical properties

General Information

· Appearance:

Form: Solid in various forms

Color: Grey
Odor: Odorless

· Odor threshold: Not determined.

· pH-value at 20 °C (68 °F): 7

· Change in condition

Melting point/Melting range: 1,713 °C (3,115.4 °F) Boiling point/Boiling range: 2,230 °C (4,046 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not determined.

• **Decomposition temperature:** Not determined.

• Auto igniting: Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

**Lower:** Not determined. **Upper:** Not determined.

· Vapor pressure: Not applicable.

• **Density at 20 °C (68 °F):** 2.64 g/cm³ (22.03 lbs/gal) (EN ISO 2811-1)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. Kinematic: Not applicable.

· Solvent content:

VOC content: 0.00 %

0.0 g/l / 0.00 lb/gal

Solids content: 100.0 %

· Other information No further relevant information available.

### 10 Stability and reactivity

- · Reactivity see Section 10.2
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 5)

· Hazardous decomposition products:

No dangerous decomposition prodocts used according to specifications.

· Additional information:

Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

### 11 Toxicological information

- · Information on toxicological effects There were no toxicological findings to the mixture.
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Subacute to chronic toxicity: not tested
- · Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

The product is not subject to classification according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
14808-60-7 Quartz (SiO2)	1
· NTP (National Toxicology Program)	
14808-60-7 Quartz (SiO2)	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not hazardous for water.
- · Results of PBT and vPvB assessment
- · PBT: Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
- · vPvB: Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

· Waste treatment methods

The waste is not hazardous. Dispose of in accordance with the regulations after consultation with the relevant local authorities and the disposal in a suitable and licensed facility.

Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.

(Contd. on page 7)



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 6)

#### · Recommendation:



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.

Cured product residues are not hazardous waste.

Smaller quantities can be disposed of with household waste.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · DOT, ADR, ADN, IMDG, IATA	Void
<ul><li>· UN proper shipping name</li><li>· DOT, ADR, ADN, IMDG, IATA</li></ul>	Void
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA · Class	Void
· Packing group · DOT, ADR, IMDG, IATA	Void
<ul><li>Environmental hazards:</li><li>Marine pollutant:</li></ul>	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Remarks:	Classification according to viscosity clause (2.2.3.1.5)
· IMDG · Remarks:	Classification according to viscosity clause (2.3.2.5)
· UN "Model Regulation":	Void

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1344-28-1 aluminium oxide

· TSCA (Toxic Substances Control Act):

14808-60-7 Quartz (SiO2)

1344-28-1 aluminium oxide

(Contd. on page 8)



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 7)

#### · Proposition 65

· Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

14808-60-7 Quartz (SiO2) 1344-28-1 aluminium oxide A2 A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz (SiO2)

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### \*16 Other information

These figures relate to the product as delivered.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Training hints

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555). Instruction must take place before the start of employment and at least annually thereafter.

Date of preparation / last revision 10/09/2018 / 30

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 9)



Printing date 10/09/2018 Reviewed on 11/11/2015

Trade name: ALT S223 Filler

(Contd. of page 8)

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

· Sources

www.gestis.de www.echa.eu logkow.cisti.nrc.ca

· \* Data compared to the previous version altered.

US-