



ROUND TOP OF DOWEL & REMOVE ALL SHARP EDGES, BURS, PAINTED PRIMER, RUST, OILS, & DIRT.

ALT R230 THIXO MEMBRANE CAP OVER TOP OF DOWEL TO FULLY ENCAPSULATE PENETRATION.

SUPPLEMENTAL COAT OF ALT R230 THIXO RESIN W/BROADCAST AGGREGATE FOR MECHANICAL PROTECTION LAYER (TYP.)

ALT VEHICULAR TRAFFIC SYSTEM AS SPECIFIED OR REQUIRED.

PREPARE, LEVEL & PATCH SUBSTRATE W/ALT R290 PASTE OR ALT RS242 MORTAR AFTER PRIMING & PRIOR TO APPLICATION OF ALT R230 THIXO MEMBRANE (TYP.)

PROTECT ALT MEMBRANE FROM MECHANICAL DAMAGE DURING DRILLING & INSTALLATION OF EPOXY ANCHOR.

NOTE:
EPOXY ANCHOR/DOWEL FLASHING SUBJECT TO MECHANICAL DAMAGE & NOT RECOMMENDED FOR USE IN SUBMERGED LOCATIONS.

1/4" (6mm)
CLEAR

4" (10cm)
(MIN.)

PROVIDE MINIMUM CLEAR ALL AROUND FOR PLACEMENT OF WHEELSTOP

POWER TOOL CLEAN DOWEL PER SSPC-SP3.

ALT R230 RESIN BEAD TYPICAL @ ALL MEMBRANE TERMINATION POINTS (TYP.)

ALT R230 MEMBRANE SKIRT WRAPPED AROUND DOWEL W/ 2" MIN. OVERLAP

DEGREASE ANCHOR W/ALT ACTIVATOR PRIOR TO APPLICATION OF ALT PRIMER OR ALT R230 THIXO RESIN (TYP.)

6"X6" MIN. ALT R230 MEMBRANE TARGET FLASHING APPLIED AROUND BASE OF DOWEL OR ANCHOR.

ALT RS233 MORTAR W/BROADCAST AGGREGATE & ALT FINISH 288 OR ALT R268 TEXTURED COATING APPLIED OVER PREPARED & PRIMED SUBSTRATE (TYP.)

316 STAINLESS STEEL EPOXY-SET ANCHOR OR DOWEL SIZED AS REQUIRED FOR CURB MOUNTING (BY OTHERS)

ANCHOR HOLE DRILLED THRU IN-PLACE ALT R230 THIXO MEMBRANE W/CARBIDE TIPPED DRILL BITS USING HAMMER DRILL IN ROTO-HAMMER MODE.

DRAWING NO.:

TN-P1

TN_P01

**VEHICULAR PARKING WHEEL STOP
ENCAPSULATED ANCHOR/DOWEL FLASHING**

REVISION	0	SCALE	N.T.S.	DRAWN BY	ALT Global
ISSUE DATE	10-15-2014				



ALT