



ROUND TOP OF DOWEL & REMOVE ALL SHARP EDGES, BURS, PAINTED PRIMER, RUST, OILS, & DIRT.

ALT R230 THIXO MEMBRANE CAP OVER TOP OF DOWEL TO FULLY ENCAPSULATE PENETRATION.

SUPPLEMENTAL COAT OF ALT R230 THIXO RESIN W/BROADCAST AGGREGATE FOR MECHANICAL PROTECTION LAYER (TYP.)

ALT VEHICULAR TRAFFIC SYSTEM AS SPECIFIED OR REQUIRED.

4" (10cm)
(MIN.)

1/4" (6mm)
CLEAR

PROVIDE MINIMUM CLEAR ALL AROUND FOR PLACEMENT OF WHEELSTOP

POWER TOOL CLEAN DOWEL PER SSPC-SP3.

ALT R230 RESIN BEAD TYPICAL @ ALL MEMBRANE TERMINATION POINTS (TYP.)

ALT R230 MEMBRANE SKIRT WRAPPED AROUND DOWEL W/ 2" MIN. OVERLAP

DEGREASE ANCHOR W/ALT ACTIVATOR PRIOR TO APPLICATION OF ALT PRIMER OR ALT R230 THIXO RESIN (TYP.)

6"X6" MIN. ALT R230 MEMBRANE TARGET FLASHING APPLIED OVER IN-PLACE ALT R230 FIELD MEMBRANE

PREPARE, LEVEL & PATCH SUBSTRATE W/ALT R290 PASTE OR ALT RS242 MORTAR AFTER PRIMING & PRIOR TO APPLICATION OF ALT R230 MEMBRANE (TYP.)

PROTECT ALT MEMBRANE FROM MECHANICAL DAMAGE DURING DRILLING & INSTALLATION OF EPOXY ANCHOR.

ALT R230 FIELD MEMBRANE APPLIED TO PREPARED & PRIMED SUBSTRATE

316 STAINLESS STEEL EPOXY-SET ANCHOR OR DOWEL SIZED AS REQUIRED FOR CURB MOUNTING (BY OTHERS)

ANCHOR HOLE DRILLED THRU IN-PLACE ALT R230 FIELD MEMBRANE W/CARBIDE TIPPED DRILL BITS USING HAMMER DRILL IN ROTO-HAMMER MODE.

NOTE:
EPOXY ANCHOR/DOWEL FLASHING SUBJECT TO MECHANICAL DAMAGE & NOT RECOMMENDED FOR USE IN SUBMERGED LOCATIONS.

DRAWING NO.:

TR-P1

TR_P01

**VEHICULAR PARKING WHEEL STOP
ENCAPSULATED ANCHOR/DOWEL FLASHING**

REVISION	0	ISSUE DATE	10-15-2014	SCALE	N.T.S.	Drawn by	ALT Global
----------	---	------------	------------	-------	--------	----------	------------

