



POLYURETHANE CAULKING  
(BY OTHERS)

COUNTERFLASHING AS REQUIRED  
(BY OTHERS)

ALT R230 THIXO MEMBRANE TARGET PATCH  
APPLIED OVER SCUPPER OPENING

PREPARE, LEVEL & PATCH SUBSTRATE  
W/ALT R290 PASTE OR RS242 MORTAR  
AFTER PRIMING & PRIOR TO APPLICATION  
OF ALT R230 MEMBRANE (TYP.)

ALT R230 RESIN BEAD TYPICAL @ ALL  
MEMBRANE TERMINATION POINTS

ALT R230 THIXO MEMBRANE 2" MINIMUM OVERLAP  
TO PROVIDE CONTINUOUS FLASHING

(1) PLY ALT R230 THIXO MEMBRANE FLASHING  
EXTEND INTO PREPARED & PRIMED TUBE W/  
OVERLAP 2" TO FORM SCUPPER FLASHING

ASSURE FULL RESIN SATURATION OF  
FLEECE & CONTACT W/SUBSTRATE.

ALT R230 MEMBRANE FIELD

**NOTE:**  
METAL OR PVC SCUPPER SLEEVE THRU  
WALL BY OTHERS. FOR SCUPPERS CAST IN  
CONCRETE TO BE LINED W/ALT MEMBRANE  
PROVIDE 4" X 4" MINIMUM OPENING (TYP.)

DRAWING NO.:

**D-1D**

AD\_01D

**PREFABRICATED TUBE THRU-WALL  
OVERFLOW SCUPPER FLASHING**

REVISION	0	ISSUE DATE	10-15-2014	SCALE	N.T.S.	DRAWN BY	ALT Global
----------	---	------------	------------	-------	--------	----------	------------

