



ACCEPTABLE ALT TRAFFIC SURFACING
SEE SPECIFICATION FOR OPTIONS.

(1) PLY ALT R230 THIXO MEMBRANE
FLASHING EXTEND MINIMUM 2" (5 CM) INTO
PREPARED & CLEANED DRAIN BOWL.

PREPARE, LEVEL & PATCH SUBSTRATE W/
ALT RS242 MORTAR AFTER PRIMING &
PRIOR TO APPLICATION OF ALT R230 THIXO
WATERPROOFING MEMBRANE (TYP.)

SET DRAIN FLANGE IN ALT RS242 MORTAR
AS REQUIRED TO CREATE A SMOOTH
TRANSITION (TYP.)

4" (10cm)
(MIN.)

ALT R230 THIXO RESIN BEAD TYPICAL
@ ALL MEMBRANE TERMINATION
POINTS.
ACCEPTABLE DECK DRAIN ASSEMBLY-ADJUST
COLLAR AS REQUIRED TO ASSURE TOP OF
GRATE IS FLUSH W/TRAFFIC SURFACE.
PREPARE DRAIN BOWL AS REQ'D. FOR
R230 THIXO MEMBRANE APPLICATION.



TYPICAL TRAFFIC DECK DRAIN

DRAWING NO.:

TN-D1

REVISION
0

ISSUE DATE
10-15-2014

SEAL
N.T.S.

DRAWN BY
ALT Global

TN_D01